

APEX 16X0,50 LE

PRODUCT DATA SHEET

This is to certify that the product supplied by us is manufactured according to quality procedures in compliance with ISO 9001, ISO14001, EN 13246.

We certify the product lead free.

Our tensile testing follows ISO 6892-1.

Produced in Sweden

Product description	Product designation:	APEX 16X0,50 LE		
	Item code:	0716050		
	Material type:	Steel		
	Material quality:	Standard		
	Surface finish:	Black painted and waxed, deburred edges		

Strap properties	Width (mm):	16	+0,05/-0,25		
	Thickness (mm):	0.5	+/-0,035		
	Elongation minimum - A100 (%):	1			
	Elongation minimum - A5 (%):	4			
	Break Strength (N):	Mini.:	6360	Average:	7150
	Tensile Strength (N/mm ²):	Mini.:	800	Average:	890

Coils details	Winding:	Ribbon wound		
	Coil Inside Diameter (mm):	300		
	Coil Outside Diameter (mm):	600		
	Coil Width (mm):	15.9		
	Approximate Gross Coil Weight (kg):	24		

Pallet details	Package Dimensions (LxWxH):	580*675*550		
	Number of Coils per Pallet:	25		
	Coils axis on pallet:	Horizontal		
	Approx. Gross Weight per Pallet (kg):	600		