# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

Article No.: 688 SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022

Version: 3.0 Revision date: 10.12.2022 EN

Version: 3.0 Issue date: 10.12.2022 Page 1 / 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. product identifiers

Article No. (manufacturer/supplier) 688

Trade name/designation SILASAN Terrassen-Oel

farblos

UFI: U79V-R5R7-899V-S83C

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

Knuchel Farben AG

Farben + Lacke Telephone: +41 (0) 32 636 50 40 Steinackerweg 11 Telefax: +41 (0) 32 636 50 45

CH-4537 Wiedlisbach

#### Department responsible for information:

laboratory Manager

E-mail (competent person) info@knuchel.ch

1.4. Emergency telephone number

Emergency telephone number 145 (+41 (0)44 251 51 51)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour.

Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### **Hazard pictograms**





#### Warning

#### **Hazard statements**

H226 Flammable liquid and vapour.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges. P273 Avoid release to the environment.

P280 Wear protective gloves and eye/face protection.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P370 + P378 In case of fire: Use extinguishing powder or sand to extinguish.

P391 Collect spillage.

P403 + P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to industrial incineration plant.

#### Hazard components for labelling

not applicable

### Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

688 Article No.: SILASAN Terrassen-Oel 27.12.2022 Print date: Revision date: 10.12.2022 Issue date: 10.12.2022 Version: 3.0

> **EUH208** Contains reaction mass of

> > α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and

Page 2 / 11

May produce an allergic reaction.

#### 2.3. Other hazards

No information available.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. **Mixtures**

Öle Description

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No. CAS No. Index No.	REACH No.  Designation  classification // Remark	weight-%
923-037-2	01-2119471991-29 Hydrocarbons, C10-C12, isoalkanes <2% aromatics Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / Aquatic Chronic 2 H411 / EUH066	40 - 60
918-481-9	01-2119457273-39 Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics Asp. Tox. 1 H304	15 - 25
271-369-5 68551-19-9	01-2119491311-45 Alkanes, C12-14-iso- Asp. Tox. 1 H304 / Aquatic Chronic 2 H411	1 - 5
919-857-5	01-2119463258-33 Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics STOT SE 3 H336 / Asp. Tox. 1 H304 / Flam. Liq. 3 H226	1 - 5
400-830-7 607-176-00-3	01-0000015075-76 reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxy poly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2 H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) Skin Sens. 1 H317 / Aquatic Chronic 2 H411	0.5 - 1

#### **Additional information**

Full text of classification: see section 16

#### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

#### Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

688 Article No.: SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022 Issue date: 10.12.2022 Version:

#### 4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

#### **SECTION 5: Firefighting measures**

#### **Extinguishing media**

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Unsuitable extinguishing media

strong water jet

#### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

Page 3 / 11

#### **SECTION 6: Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

#### 62 **Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

#### Reference to other sections

Observe protective provisions (see section 7 and 8).

### **SECTION 7: Handling and storage**

#### Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools, Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

### **Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

#### Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

## Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

Article No.: 688 SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022 Version: 3.0 Issue date: 10.12.2022

Observe technical data sheet. Observe instructions for use.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limit values:

not applicable

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Page 4 / 11

#### Personal protection equipment

#### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Hand protection

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)

Thickness of the glove material > 0.4 mm; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye/face protection

Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state:

Colour:

Colour:

Characteristic

Codour threshold:

Melting point/freezing point:

Liquid

refer to label

characteristic

not applicable

not applicable

Initial boiling point and boiling range: 150 °C

Source: Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Flammable liquid and vapour.

Lower and upper explosion limit:

Lower explosion limit: 0.8 Vol-% Upper explosion limit: 7 Vol-%

Source: Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Flash point: 40 °C

Method: DIN 53213

Auto-ignition temperature: 230 °C

Source: Alkanes, C12-14-iso-

Decomposition temperature: not applicable pH at 20 °C: not applicable Cinematic viscosity (40°C): 20 mm²/s

Viscosity at 20 °C: 12 - 16 sec DIN 4 mm

Solubility(ies):

Water solubility at 20 °C: insoluble

Version:

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 688 SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022

Partition coefficient: n-octanol/water: see section 12

Issue date: 10.12.2022

Vapour pressure at 20 °C: 5 mbar

Source: Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Page 5 / 11

Density and/or relative density:

Density at 20 °C:

Relative vapour density:

particle characteristics:

0.83 g/cm³

not applicable

9.2. Other information

Solid content: 29 weight-%

solvent content:

Organic solvents: 71 weight-% Water: 0 weight-%

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

#### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Hazardous decomposition byproducts may form with exposure to high temperatures.

#### 10.5. Incompatible materials

not applicable

#### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

## Acute toxicity

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

oral, LD50, Rat: > 15000 mg/kg dermal, LD50, Rabbit: > 3160 mg/kg

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (dust and mist), LC50, Rat: > 5 mg/L (4 h)

Method: OECD 403

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

oral, LD50, Rat: > 5000 mg/kg

Method: OECD 401

dermal, LD50, Rat: > 3000 mg/kg dermal, LD50, Rabbit: > 5000 mg/kg

Method: OECD 402

inhalative (vapours), LC50, Rat: > 9,3 mg/L (4 h)

Alkanes, C12-14-iso-

oral, LD50, Rat: > 5000 mg/kg

dermal, LD50, Rabbit: > 2000 mg/kg

inhalative (vapours), LC50, Rat 4,6 - 7,64 mg/L (4 h)

Skin corrosion/irritation; Serious eye damage/eye irritation

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 688 SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022 Version: 3.0 Issue date: 10.12.2022

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Skin (4 h)

Based on available data, the classification criteria are not met.

eyes

Based on available data, the classification criteria are not met.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Skin (4 h)

Repeated exposure may cause skin dryness or cracking.

eves

No data available

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Skin (4 h)

Based on available data, the classification criteria are not met.

eyes

Causes serious eye irritation.

Alkanes, C12-14-iso-

Skin (4 h)

In rare cases the product can cause temporary erythema of the skin.

eves

Causes slight eye irritation

#### Respiratory or skin sensitisation

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Skin: ; Evaluation Based on available data, the classification criteria are not met.

Respiratory system: ; Evaluation Based on available data, the classification criteria are not met.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Skin:

Based on available data, the classification criteria are not met.

Respiratory system:

No data available

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Skin: ; Evaluation Based on available data, the classification criteria are not met.

Respiratory system: ; Evaluation Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-

Skin:

Not to be expected skin or respiratory diseases.

Respiratory system:

An inhalation hazard may only arise if product is used in aerosol conditions or if heated up. If material is misted or if vapors are generated from heating, exposure may cuase irritation of mucous membranes and upper respiratory tract. Based on data from similar materials.

EN Page 6 / 11

#### CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Germ cell mutagenicity; Evaluation Based on available data, the classification criteria are not met.

Carcinogenicity: Evaluation Based on available data, the classification criteria are not met.

Reproductive toxicity; Evaluation Based on available data, the classification criteria are not met.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

Lactation

No data available

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Germ cell mutagenicity: Evaluation Based on available data, the classification criteria are not met.

Carcinogenicity; Evaluation Based on available data, the classification criteria are not met.

Reproductive toxicity; Evaluation Based on available data, the classification criteria are not met.

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 688 SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022 Version: 3.0 Issue date: 10.12.2022

Alkanes, C12-14-iso-

Germ cell mutagenicity; Evaluation No mutagenicity Carcinogenicity; Evaluation No cancer production Reproductive toxicity; Evaluation No reproductive toxicity

#### STOT-single exposure; STOT-repeated exposure

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Specific target organ toxicity (single exposure) Evaluation Based on available data, the classification criteria are not met. Specific target organ toxicity (repeated exposure) Evaluation Based on available data, the classification criteria are not met.

Page 7 / 11

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Specific target organ toxicity (single exposure)

May cause drowsiness or dizziness.; After absorption: cardiovascular disorders, cyanosis, agitation After absorption of large quantities: Drowsiness. CNS disorders Other dangerous properties cannot be excluded.

Specific target organ toxicity (repeated exposure)

No data available

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Specific target organ toxicity (single exposure) Evaluation Based on available data, the classification criteria are not met. Specific target organ toxicity (repeated exposure) Evaluation Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-

Specific target organ toxicity (single exposure)

No data available

Specific target organ toxicity (repeated exposure)

No data available

#### **Aspiration hazard**

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Aspiration hazard; Evaluation May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Aspiration hazard

Aspiration can lead to pulmonary edema and pneumonia.; May be fatal if swallowed and enters airways.

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Aspiration hazard; Evaluation Based on available data, the classification criteria are not met.

Alkanes, C12-14-iso-

Aspiration hazard

May be fatal if swallowed and enters airways.; If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

#### Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### 11.2. Information on other hazards

#### **Endocrine disrupting properties**

No information available.

#### **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Fish toxicity, LC50, Pimephales promelas (fathead minnow): 220 mg/L (96 h)

Daphnia toxicity, LC50, crangon crangon: 4,3 mg/L (96 h)

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 688 SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022 Version: 3.0 Issue date: 10.12.2022

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics Daphnia toxicity, NOEC, Oncorhynchus mykiss (Rainbow trout): 0,21 mg/L (28 d)

FN

Page 8 / 11

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Fish toxicity, LL0, Oncorhynchus mykiss (Rainbow trout): 1000 mg/L (96 h)

Algae toxicity, EL0, green alga: 1000 mg/L (72 h)
Daphnia toxicity, EL0, Daphnia magna: 1000 mg/L (48 h)
Algae toxicity, NOELR, green alga: 1000 mg/L (72 h)
Daphnia toxicity, NOELR, Daphnia magna: 1 mg/L (21 d)

Alkanes, C12-14-iso-

Fish toxicity, LL50:: > 750 mg/L

#### Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics Daphnia toxicity, NOEC, Daphnia magna (Big water flea): 0,02 mg/L (21 d) Method: OECD 211

#### 12.2. Persistence and degradability

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Biodegradation: Evaluation Not readily biodegradable (according to OECD criteria)

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics Biodegradation: Evaluation Not readily biodegradable (according to OECD criteria)

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Biodegradation: Evaluation Readily biodegradable (according to OECD criteria).

Alkanes, C12-14-iso-

Biodegradation: Evaluation Not readily biodegradable (according to OECD criteria)

#### 12.3. Bioaccumulative potential

Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics

Partition coefficient: n-octanol/water:

No further relevant information available.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics

Distribution coefficient n-octanol/water (log KOW):

No data available

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

Distribution coefficient n-octanol/water (log KOW):

No data available

Alkanes, C12-14-iso-

Distribution coefficient n-octanol/water (log KOW):

This product evaporates.; This product seeps through soils into the groundwater.

#### 12.4. Mobility in soil

 $Hydrocarbons,\,C10\text{-}C13,\,n\text{-}alkanes,\,iso\text{-}alkanes,\,cyclic,\,<\!\!2\%\,\,aromatics$ 

soil:

No further relevant information available.

Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics soil:

No data available

Hydrocarbons, C10-C12, isoalkanes <2% aromatics

soil:

No data available

Alkanes, C12-14-iso-

soil:

No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

No information available.

# according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878

Article No.: 688 SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022

Version: 3.0 Issue date: 10.12.2022 Page 9 / 11

#### 12.7. Other adverse effects

No information available.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Appropriate disposal / Product

#### Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste. Dispose of waste according to applicable legislation.

#### List of proposed waste codes/waste designations in accordance with EWC

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

#### Appropriate disposal / Package

#### Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

#### **SECTION 14: Transport information**

14.1. UN number or ID number

UN 1263

14.2. UN proper shipping name

Land transport (ADR/RID): Paint Sea transport (IMDG): PAINT Air transport (ICAO-TI / IATA-DGR): Paint

14.3. Transport hazard class(es)

3

14.4. Packing group

Ш

14.5. Environmental hazards

Land transport (ADR/RID) UMWELTGEFÄHRDEND

Marine pollutant p

#### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

#### **Further information**

#### Land transport (ADR/RID)

Tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E. S-E

in packages <= 5 litres not restricted 2.10.2.7

#### 14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

#### **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU** legislation

#### Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L): 589

#### **National regulations**

### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable.

# according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 688 SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022 Version: 3.0 Issue date: 10.12.2022

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Page 10 / 11

#### 15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

EC No. CAS No.	Designation	REACH No.
923-037-2	Hydrocarbons, C10-C12, isoalkanes <2% aromatics	01-2119471991-29
918-481-9	Hydrocarbons, C10-C13, n-alkanes, iso-alkanes, cyclic, <2% aromatics	01-2119457273-39
271-369-5 68551-19-9	Alkanes, C12-14-iso-	01-2119491311-45
919-857-5	Hydrocarbons, C9-C11, n-alkanes, iso-alkanes, cyclic compounds, <2% aromatics	01-2119463258-33
400-830-7	reaction mass of $\alpha$ -3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propiony $\omega$ -hydroxypoly(oxyethylene) and $\alpha$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propiony $\omega$ -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionylo xypoly(oxyethylene)	I

#### **SECTION 16: Other information**

#### Full text of classification in section 3

Flam. Liq. 3 / H226 Flammable liquids Flammable liquid and vapour.

Asp. Tox. 1 / H304 Aspiration hazard May be fatal if swallowed and enters airways. Aquatic Chronic 2 / H411 Hazardous to the aquatic environment Toxic to aquatic life with long lasting effects.

STOT SE 3 / H336 STOT-single exposure May cause drowsiness or dizziness. Skin Sens. 1 / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]
Flam. Liq. 3 Flammable liquids On basis of test data.

Aquatic Chronic 2 Hazardous to the aquatic environment Calculation method.

### Abbreviations and acronyms

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL Occupational Exposure Limit Value

BLV Biological Limit Value CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging CMR Carcinogenic, Mutagenic and Reprotoxic

DIN German Institute for Standardization / German industrial standard

DNEL Derived No-Effect Level

EAKV European Waste Catalogue Directive

EC Effective Concentration
EC European Community
EN European Standard

IATA-DGR International Air Transport Association – Dangerous Goods Regulations

IBC Code International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk ICAO-TI International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous

Goods by Air

IMDG Code International Maritime Code for Dangerous Goods ISO International Organization for Standardization

LC Lethal Concentration

LD Lethal Dose

MARPOL Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD Organisation for Economic Cooperation and Development

PBT persistent, bioaccumulative, toxic
PNEC Predicted No Effect Concentration

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

UN United Nations

VOC Volatile Organic Compounds

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Article No.: 688 SILASAN Terrassen-Oel Print date: 27.12.2022 Revision date: 10.12.2022 Version: 3.0 Issue date: 10.12.2022

vPvB very persistent and very bioaccumulative

#### **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

EN Page 11 / 11