



COOL-FIT 4.0 Rohr, d32-d225

Ausführung:

- vorisoliertes PE100 SDR 11/17 metrisch
- Isolation aus GF HE Schaum
- Schlagfest Farbe: schwarz
- Länge: 5m
- Mit freien Enden für Elektroschweissung

d/D (mm)	DN (mm)	SDR	PN (bar)	Code	SP	Gewicht (kg)	di (mm)	L (mm)	L1 (mm)
32/90	25	11	16	738 173 108	5		26.2	5000	36
40/110	32	11	16	738 173 109	5		32.6	5000	40
50/110	40	11	16	738 173 110	5		40.8	5000	44
63/125	50	11	16	738 173 111	5		51.4	5000	48
75/140	65	11	16	738 173 112	5		61.4	5000	55
90/160	80	11	16	738 173 113	5		73.6	5000	62
110/180	100	11	16	738 173 114	5		90.0	5000	72
160/250	150	17	10	738 173 117	5		141.0	5000	90
225/315	200	17	10	738 173 120	5		198.2	5000	110

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>